

## **Spoton Spray Tip Pressure Tester** RSC28040





## **Details**

Accurately check nozzle pressure between the nozzle and nozzle body, verify accuracy of sprayer pressure sensor or gauge and find blockages in hoses and booms. This gauge features a digital display in PSI, Bars or kPa. Uses industry standard quick connects. Operates with a simple one button operation. Shock proof rubber covering protects against drops. LCD shows range & Units: 3.0 - 160.0 PSI, 0.20 - 11.00 Bars, 20 - 1100 kPa. Accuracy: +/- 2% or +/- 1 PSI. Includes battery.

- Check nozzle pressure between the nozzle and nozzle body
- Verify Accuracy of Sprayer Pressure Sensor or Gauge
- Simple one button operation
- Simple One Button Operation
- Verify accuracy of sprayer pressure sensor or gauge
- Digital Display: 0.5 PSI, 0.05 BAR, 5 kPa
- Find blockages in hoses and booms
- Shock Proof Rubber Covering
- Accuracy: Greater of +/-1% of reading or +/-0.5 PSI, +/-0.5 Bars, or +/-5 kPa
- Uses Industry Standard Quick Connects
- Uses industry standard quick connects
- Find Blockages in Hoses and Booms
- Shock proof rubber covering protects against drops
- Installs Between Nozzle and Nozzle Body
- Display resolution: 0.5 PSI, 0.05 Bars, 5 kPa
- Includes Battery
- Includes 5 year battery
- Range: 3.0 160.0 PSI, 0.20 11.00 BAR, 20 -1100 kPa



## **Spoton Spray Tip Pressure Tester**



RSC28040

**Specifications** 

Manufacturer Pressure Range SpotOn 10-160.0 PSI, 0.20-11.00 Bars, 20-1100 kPa

MecaGreen

Rue des Praules 1A Gembloux, 85714 +32 81 61 70 13

https://mecagreen.rrproducts.com/